





■ TDB 2x7-125A



■ TDB 2x11-125A



Technical data	TDB 2x7-125A		TDB 2x11-125A	
	Voltage(V)	Current(A)	Voltage(V)	Current(A)
IEC 60947-7-1	500	125	500	125
IEC 60947-7-1 rated data				
Impulse voltage (kV)	4		4	
Pollution degree/Voltage category/Material group	3 / III / I		3 / III / I	
I _{cu} (kA)	4.5		4.5	
I _{pk} (kA)	20		20	

Description		Type	Ordering No.	Qty.	Type	Ordering No.	Qty.
Terminal block, for mounting on TH 35-7.5, 15 		TDB 2x7-125A	8037000230	1	TDB 2x11-125A	8037000231	1
Connection data							
Input		Line			Line		
Connection Points		1			2		
Diameter (mm)		8.5			8.5		
Connection capacity	Rigid (mm²)	10 – 35			10 – 35		
	Flexible (mm²)*	10 – 25			10 – 25		
	(AWG)	8 – 2			8 – 2		
Tightening torque (N·m)		2 – 3			2 – 3		
Stripping length (mm)		8 – 10			8 – 10		
Output		Load 1			Load 1		
Connection Points		1			2		
Diameter (mm)		7.5			7.5		
Connection capacity	Rigid (mm²)	10 – 25			2.5 – 6		
	Flexible (mm²)*	6 – 16			1.5 – 6		
	(AWG)	8 – 4			8 – 4		
Tightening torque (N·m)		2 – 3			2 – 3		
Stripping length (mm)		8 – 10			8 – 10		
Output		Load 2			Load 2		
Connection Points		5			7		
Diameter (mm)		5.3			5.3		
Connection capacity	Rigid (mm²)	2.5 – 6			2.5 – 6		
	Flexible (mm²)*	1.5 – 6			1.5 – 6		
	(AWG)	14 – 10			14 – 10		
Tightening torque (N·m)		2 – 3			2 – 3		
Stripping length (mm)		8 – 10			8 – 10		
Color	Body	Gray			Gray		
	Cover	Dark gray			Dark gray		
Dimensions (mm)		W / L / H			W / L / H		
Width/Length/Height		64/50/50			100/50/50		
Insulation material							
Body		PA 6.6 / V-0			PA 6.6 / V-0		
Cover		PC			PC		

*Prepare this kind of cable with ferrule.