




TDB 2x15-125A



CE



Technical data	TDB 2x15-125A	
	Voltage(V)	Current(A)
IEC 60947-7-1	500	125
IEC 60947-7-1 rated data		
Impulse voltage (kV)	4	
Pollution degree/Voltage category/Material group	3 / III / I	
I _{cw} (kA)	4.5	
I _{pk} (kA)	20	

Description		Type	Ordering No.	Qty.
Terminal block, for mounting on TH 35-7.5, 15 		TDB 2×15-125A	8037000232	1
Connection data				
Input		Line		
Connection Points		2		
Diameter (mm)		8.5		
Connection capacity	Rigid (mm²)	10 – 35		
	Flexible (mm²)*	10 – 25		
	(AWG)	8 – 2		
Tightening torque (N·m)		2 – 3		
Stripping length (mm)		8 – 10		
Output		Load 1		
Connection Points		2		
Diameter (mm)		7.5		
Connection capacity	Rigid (mm²)	10 – 25		
	Flexible (mm²)*	6 – 16		
	(AWG)	8 – 6		
Tightening torque (N·m)		2 – 3		
Stripping length (mm)		8 – 10		
Output		Load 2		
Connection Points		11		
Diameter (mm)		5.3		
Connection capacity	Rigid (mm²)	2.5 – 6		
	Flexible (mm²)*	15 – 6		
	(AWG)	14 – 10		
Tightening torque (N·m)		2 – 3		
Stripping length (mm)		8 – 10		
Color	Body	Gray		
	Cover	Dark gray		
Dimensions(mm)		W / L / H		
Width/Length/Height		130/50/50		
Insulation material				
Body		PA 6.6 / V-0		
Cover		PC		

*Prepare this kind of cable with ferrule.